

## TECHNICAL INFORMATION PRELIMINARY



- Common Paper PSA Label -

### Gloss Art90/RV20T/GG62

#### PHYSICAL CHARACTERISTICS

##### Facestock

A white and glossy machine coated super-calendered woodfree printing paper. The coated facestock offers top print quality by all conventional printing processes.

Basis weight ISO 536 : 90 gsm  
Caliper ISO 534 : 72  $\mu\text{m}$

##### Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : -12°C  
Product Functional Service Temperature: -30°C / +80°C

##### Liner

A super-calendered blue glassine paper.

Basis weight ISO 536 : 62 gsm  
Caliper ISO 534 : 55  $\mu\text{m}$

#### PERFORMANCE CHARACTERISTICS

| Properties                  | Test Method | Typical values      |
|-----------------------------|-------------|---------------------|
| Initial Tack on Glass       | FINAT FTM9  | 5.0 N/25mm          |
| Adhesion to Stainless Steel | FINAT FTM1  | 2.5 N/25mm (20mins) |
| Total Product Caliper       | ISO 534     | 140 $\mu\text{m}$   |

##### Shelf life

1 year when stored at 22°C and 50% RH