

TECHNICAL INFORMATION



- Wine Label -

Malian/WL01/WG62

PHYSICAL CHARACTERISTICS

Facestock

A matte white BOPP film with special resin filler surface to provide excellent thermal transfer printability and tensile strength. Can be printed by normal lithographic ink, letterpress, screen, flexo and gravure using UV, solvent or water-based inks. Compatible with thermal transfer resin-based or resin/wax combination ribbons.

Caliper ISO 534 : 75 μm

Adhesive

A general purpose acrylic permanent adhesive with excellent clarity and aging resistance. It has good tack to low surface energy substrates. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, GEN EN71, PART 3.

Minimum Application Temperature : +5°C
Product Functional Service Temperature: -20°C / +80°C

Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 60 gsm
Caliper ISO 534 : 54 μm

Performance Characteristics

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	12.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	6.0 N/25mm (20mins)
Total Product Caliper	ISO 534	149 μm

Shelf life

1 year when stored at 22°C and 50% RH