

## TECHNICAL INFORMATION



- Common Paper PSA Label -

## Matte Art90/RV23N/WG62

### PHYSICAL CHARACTERISTICS

#### Facestock

A matte-coated super-calendared woodfree printing paper. Suitable for print with all conventional printing processes.

Basis weight ISO 536 : 90 gsm  
Caliper ISO 534 : 82  $\mu\text{m}$

#### Adhesive

A removable acrylic adhesive designed with long removability time frame on substrate such as stainless steel, aluminum and polycarbonate. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing.

Minimum application temperature : -10°C  
Product Functional Service temperature : -30°C / +70°C

#### Liner

A super-calendared white glassine paper.

Basis weight ISO 536 : 60 gsm  
Caliper ISO 534 : 54  $\mu\text{m}$

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	3.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	1.3 N/25mm (20mins)
Total Product Caliper	ISO 534	146 $\mu\text{m}$

#### Shelf life

1 year when stored at 22°C and 50% RH