

## TECHNICAL INFORMATION PRELIMINARY



- Common Paper PSA Label -

### Super White Gloss/RV20P/WK80

#### PHYSICAL CHARACTERISTICS

##### Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm  
Caliper ISO 534 : 88 µm

##### Adhesive

An emulsion acrylic removable adhesive designed for general purpose removability on a wide variety of substrates. Features good initial tack with superior removability. Meets FDA indirect food contact requirements (21 CFR 175.105) and ECC compliant with European Toy Safety Legislation 88/378/EEC, CEN EN71, Part 3.

Minimum Application Temperature : -12°C  
Product Functional Service Temperature: -30°C / +80°C

##### Liner

A white densified clay coated Kraft paper.

Basis weight ISO 536 : 80 gsm  
Caliper ISO 534 : 80 µm

#### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	5.0 N/25mm
Adhesion on Stainless Steel	FINAT FTM1	4.5 N/25mm (20mins)
Total Product Caliper	ISO 534	186 µm

##### Shelf life

1 year when stored at 22°C and 50% RH