



- Common Paper PSA Label -

Vellum Foil Barrier66/WP04W/WK80

PHYSICAL CHARACTERISTICS

Facestock

A matte brilliant white woodfree printing paper laminated with a silver foil at reverse side. It can be printed by all conventional printing process.

Basis weight ISO 536 : 66 gsm
Caliper ISO 534 : 63 μm

Adhesive

A general purpose acrylic permanent adhesive with excellent clarity and aging resistance. It has good tack to low surface energy substrates. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : +5°C
Product Functional Service Temperature: -20°C / +80°C

Liner

A white densified clay coated kraft paper.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 75 μm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	15.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	6.5 N/25mm (20mins)
Total Product Caliper	ISO 534	160 μm

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y07042017
Rev02

