Technical specification sheet

Ball & Doggett

ballanddoggett.com.au



- Wine Label -WS Glacier/WL01/WG62

APPLICATION

Specifically designed for wine labeling application with ice bucket performance.

PHYSICAL CHARACTERISTICS

Facestock

A smooth and white uncoated paper with an untreated natural finish. Suitable for offset, flexo and hot stamping printing process.

Basis Weight	ISO 536	: 92 gsm
Caliper	ISO 534	: 98 µm

Adhesive

A general purpose acrylic permanent adhesive with excellent clarity and aging resistance. It has good tack to low surface energy substrates. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : +5°C Product Functional Service Temperature: -20°C / +80°C

Liner

A super-calendered white glassine paper.

Basis weight	ISO 536	: 60 gsm
Caliper	ISO 534	: 54 µm

PERFORMANCE CHARACTERISTICS			
Properties	Test Method	Typical values	
Initial Tack on Glass	FINAT FTM9	10.0 N/25mm	
Adhesion to Stainless Steel	FINAT FTM2	6.0 N/25mm (20mins)	
Total Product Caliper	ISO 534	169 μm	

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

