Technical specification sheet

Ball & Doggett ballanddoggett.com.au

TECHNICAL INFORMATION **PRELIMINARY**



-Wine Label-

WS Ivory/WL01/WG62

PHYSICAL CHARACTERISTICS

Facestock

Woodfree paper with high opacity and wet strength features. It is suitable for offset, flexo, silk screen and stamping printing process.

Basis Weight ISO 536 : 90 gsm Caliper ISO 534 : 126 µm

Adhesive

A general purpose emulsion acrylic permanent with excellent water resistance and develop very good adhesion on paper facestock. Features excellent initial tack and adhesion even when applied to low surface energy substrates.

Minimum Application Temperature : +5°C

Product Functional Service Temperature: -20°C / +80°C

Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 60 gsm Caliper ISO 534 : 54 µm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	13.0-16.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	7.0 N/25mm (20mins)
Total Product Caliper	ISO 534	197 μm

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended





