

## TECHNICAL INFORMATION VERSION 0.0



- Wine Label -

## White Burgundy 100/WL01/WG62

### PHYSICAL CHARACTERISTICS

#### Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 100 gsm  
Caliper ISO 534 : 110 µm

#### Adhesive

A general purpose acrylic permanent adhesive with excellent clarity and aging resistance. It has good tack to low surface energy substrates. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : +5°C  
Product Functional Service Temperature: -20°C / +80°C

#### Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 60 gsm  
Caliper ISO 534 : 54 µm

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	13.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	5.5 N/25mm (20mins)
Total Product Caliper	ISO 534	176 µm

#### Shelf life

1 year when stored at 22°C and 50% RH