

Technical specification sheet **Ball & Doggett**

ballanddoggett.com.au

- Description:** Finoset is a calendered, opaque, flexible PVC sheeting specially formulated for printing. It has specifically been designed to remain stable whilst printing to enable good registration. It has a very light emboss for ease of printing.
- Application:** Printed Binders, Industrial tags, Business Card Holders, Travel Wallets, Bunting
- Features & Benefits:** Weld able to other Plasticized PVC's
Consistency & Strength of Weld
Printing applications: Screen, UV Offset, UV inkjet.

		THICKNESS (mm)	WIDTH (mm)	LENGTH / ROLL (MTRS)
FINOSET		0.32	1350mm	
ITEM		UNIT	RESULT	METHOD
Gauge		%	± 8	ASTM-D-1593
Tolerance Width		mm	± 5	
Tolerance Tensile Strength	MD	Kg/cm ²	≥ 190	ASTM - D882A
	CD		≥ 170	
Elongation	MD	Psi	210≥	ASTM - D882A
	CD		≥ 220	
Tear Resistance	MD	Kg/mm	≥ 7.0	ASTM - D1004
	CD		≥ 7.0	
Plasticizer (DOP)		PHR	38	-
Dimensional Stability	MD	%	≤ 4.5	ASTM - D1204
Density		-	1.36	ASTM - D792

The Information given is based upon our manufacturers knowledge and experience; it is not a guarantee or legal warranty. It is important that each application is tested to confirm suitability.