ballanddoggett.com.au

# oxygen

## Product: Oxygen Coated Paper

## Category: Display & Visual - Latex, Solvent, UV Ink jet

#### Country of Origin: Korea

#### Technical specifications:

Parameters	Unit	Range
Thickness	ums	195
Basis weight	g/m2	230
Base material	Paper	
Surface	Matte	
Caliper	192micron	ASTM D645
Gloss	60° : 87.7 / 85° : 92.1	ASTM D2457
L.a.b	85 / 0 / -6	ANSI T (D50/2º/Abs/No)

Guidelines	
Printing Tip	Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%It is recommended to set up pre and post heaters around 30°C(86°F). It is necessary to dry up and not to overlap the printed material before drying up.
Lamination:	Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended.
Storage:	lt is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH
Shelf Life:	One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.

Conversion+				
<ul> <li>Flat bed cutters</li> <li>Friction bed cutters</li> </ul>	<ul><li>Cold overla</li><li>Aqueous (d</li></ul>	iminating lye & pigment)		
Die cutters	Latex			
Thermal transfer screen	Solvent			
Screen printing	Eco Solvent			
Printing offset	🔳 UV Ink jet			
<sup>+</sup> Always test with your combi	nation of printer a	nd inks prior to commerical use		
Roll Sizes				
1372mm x 50m, Matt	124811	1372mm x 50mm, Gloss	124812	
1524mm x 50m. Matt	124812			
Common Applications				

Common Applications	
Posters	Fine art reproduction
Photo realistic prints	Kiosks POP Printing