

Product: Rhino Aqueous Blockout Film BA100



Category: Sign, Display & Digital - Aqueous

Country of Origin: Korea

Technical specifications:

Parameters	Unit	Range
Thickness	ums	240
Basis weight	g/m2	215
Base material	Polyethylene (PET) / Polypropylene (PP)	
Opacity	%	100
Coating	Porous	-
Lamination	optional	-
Printing Temperature	Degree	15~30°C
	Humidity	30~60 %

Conversion⁺

- | | |
|--|---|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminating |
| <input type="checkbox"/> Friction bed cutters | <input checked="" type="checkbox"/> Aqueous (dye & pigment) |
| <input type="checkbox"/> Die cutters | <input type="checkbox"/> Latex |
| <input type="checkbox"/> Thermal transfer screen | <input type="checkbox"/> Solvent |
| <input type="checkbox"/> Screen printing | <input type="checkbox"/> Eco Solvent |
| <input type="checkbox"/> Printing offset | <input checked="" type="checkbox"/> UV Ink jet |

⁺Always test with your combination of printer and inks prior to commercial use

Roll Sizes

914mm x 30m	148957
1067mm x 30m	148958
1270mm x 30m	148959

Common Applications

Roll up stands
Indoor POS/POP Signage
Instruction plates shop & Exhibition works
Tradeshows panels
Posters