

Product: Sapphire PET Backlit Film Solvent Matt SO600**Category:** Display & Visual - Solvent, Eco Solvent, UV Ink jet

Technical specifications:

Parameters	Unit	Range
Caliper	ums	205
Basis weight	g/m2	275
Base material	Polyethylene terephthalate	
Surface	Semi matte	-
Gloss	5/8	ASTM D645
L.a.b.	85/1/-7	ANSI T D50/2 ⁹ /Abs/No

Guidelines

- Printing Tip** Dry time will vary depending on ink type.
It is necessary to dry up and not to overlap the printed material.
- Lamination:** Lamination is optional. In order to protect the image from physical damage, overlaminates is recommended.
- Storage:** It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~30°C (50°~86°F), Humidity 35~65% RH
- Shelf Life:** One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

Conversion⁺

- | | |
|--|--|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminating |
| <input type="checkbox"/> Friction bed cutters | <input type="checkbox"/> Aqueous (dye & pigment) |
| <input type="checkbox"/> Die cutters | <input checked="" type="checkbox"/> Latex |
| <input type="checkbox"/> Thermal transfer screen | <input checked="" type="checkbox"/> Solvent |
| <input type="checkbox"/> Screen printing | <input checked="" type="checkbox"/> Eco Solvent |
| <input type="checkbox"/> Printing offset | <input checked="" type="checkbox"/> UV Ink jet |

⁺Always test with your combination of printer and inks prior to commercial use

Roll Sizes

1270mm x 30m	120598
1370mm x 30m	122217
1520mm x 30m	120599

Common Applications

Light box graphic	Luminous advertising
Backlit Trade show display	Bus shelter
Department store display	Metro illuminated signage