

**Product:** Adestor Vellum Freezer

**Adestor**

**Category:** Folio Papers - Self Adhesive

**Country of origin:** Spain

## Technical specifications:

FACESTOCK

### Offset

*Description* Supercalendered uncoated woodfree paper.

*Applications* Ideal for all types of applications: variable label information (barcodes, expiry date, price, weight etc.)

*Printing techniques* Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, laser, hot stamping.

Property	Norm	Units	Value	Tolerance
Substance	75	g/m <sup>2</sup>	75	70-76
Thickness	ISO 534	µm	70	± 2
Bekk smoothness	ISO 5627	s	≥ 250	
Brightness ISO	ISO 2470-2	%	101.5	± 2
Whiteness CIE	ISO 11475	%	158.2	± 5
Opacity	ISO 2471	%	89	-2
Tensile strength MD/CD	ISO 1924-2	kN/m	5.0/3.0	-1

## Certificates

### Product approvals and usage certificates

[Contact with foodstuff \(BfR XXXVI\) - Facestock and Liners \(paper\)](#)

[Toy safety European directive 2009/48/CE](#)

[Packaging and packaging waste Directive 94/62/CE](#)

[Electric and electronic equipment \(RoHS\) Directive 2002/95/CE](#)

- \* Values are subject to change without notice. Last updated 4/4/2012.
- \* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Product: Adestor CG349

Adestor

Category: Folio Papers - Adhesive Sheets

## Technical specifications:

ADHESIVE

CG349

*Description* Acrylic permanent adhesive for frozen and cold surfaces. Should not be exposed to high temperatures and direct UV light.

*Shelf life* From the date of manufacture 1 year in 20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	13,7	≥ 10,3
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	35	≥ 20
Tack (Quick Stick stainless steel)	FTM 9	N	10,8	≥ 7,8
Minimum labelling temperature		°C	-35	
Minimum service temperature		°C	-40	
Maximum service temperature.		°C	+60	

## Certificates

### Product approvals and usage certificates

Direct contact with foodstuffs (ISEGA) - Adhesives

EN 71-3 Toy safety

Packaging and packaging waste Directive 94/62/CE

- Values are subject to change without notice. Last updated 7/28/2014.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Product: Adestor WK80

**Adestor**

Category: Folio Papers - Adhesive Sheets

## Technical specifications:

LINER

**WK80**

*Description* One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back

*Color* White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	80	±4%
Thickness	ISO 534	µm	81	±4
Tensile strength MD/CD	ISO 1924-2	kN/m	4,6 / 2,3	-0,6 / -0,3

## Certificates

### Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS) Directive 2002/95/CE

- Values are subject to change without notice. Last updated 7/27/2015.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.