Technical specification sheet B

Ball & Doggett

ballanddoggett.com.au

Product: Range: Digi Tuff Synthetic Specialty Heavy Frost

Category: Small Format Digital - Synthetic

Country of Origin: United Kingdom Website: sales@kernowcoatings.com

Technical specifications:

195HHF

Matt Heavy Frost Film

- Double sided, diffusion coated polyester with high anti-static properties
- Waterproof, tear-proof, greaseproof, can be hole punched
- Optimum balance between translucency & whiteness
- Primarily for backlight applications such as vending machines & menu boards

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (195µ/7.7mil) Weight (260gsm)

Digital Compatibility

- Colour Laser Printers & Copiers
- Dry toner

Applications Include

- Price labels
- Direct mail applications
- Warning stickers
- · POS applications
- Marketing signage

