

**Product:** Range: Digi Tuff Synthetic Specialty Light Frost

**Category:** Small Format Digital - Synthetic

**Country of Origin:** United Kingdom

**Website:** sales@kernowcoatings.com

## Technical specifications:

### 195HLF

#### Light Frost Film

- Double-sided, diffusion coated polyester with high anti-static properties
- Smooth matt surface giving a strong image & excellent ink adhesion
- No need to laminate
- Suitable for frosted binder covers & tear resistant overlays
- Great for backlit applications such as vending machines & menu boards

#### Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

#### Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (195µ/7.7mil) Weight (265gsm)

#### Digital Compatibility

- Colour Laser Printers & Copiers
- Dry toner

#### Applications Include

- Price labels
- Direct mail applications
- Warning stickers
- POS applications
- Marketing signage