

Product Specification sheet



Product: Tacky Indigo - Ultra Removable Vinyl

Category: Small Format Digital | Self Adhesive

Country of Origin: United States of America

A flexible, calendered, low tack vinyl film

Technical specifications:

White Removable

Facesheet

Type: 100micron Matt White Calendered Vinyl

Thickness: 290micron

Release liner

Type: Kraft PE

Weight: 170gsm

Thickness: 180micron

Adhesive

Type: Low-Tack Removable Acrylic

Minimum application temperature: 7°C

Temperature range: -23°C to +48°C

General

Shelf Life: 2yrs stored 21°C & 50% relative humidity

Durability: Up to 2 years (indoors)

These characteristics are average values supplied for guidance purposes

Certificates

- Certified for HP Indigo
- B2 (508 x 736) Compatible for HP Indigo

Applications Include

This product is intended for indoor/outdoor applications. Ideal for interior exterior marking or decal in applications requiring easy removability. An alternative to flood coating clear film with white ink. Excellent water resistance & good for most petroleum solvents and lower aliphatic alcohols.

Clear Removable

Facesheet

Type: 100micron Clear Calendered Vinyl

Thickness: 290micron

Release liner

Type: Kraft PE

Weight: 170gsm

Thickness: 180micron

Adhesive

Type: Low-Tack Removable Acrylic

Minimum application temperature: 2°C

Temperature range: -23°C to +65°C

General

Shelf Life: 2yrs stored 21°C & 50% relative humidity

Durability: Up to 2 years (indoors)

These characteristics are average values supplied for guidance purposes

Certificates

- Certified for HP Indigo
- B2 (508 x 736) Compatible for HP Indigo

Applications Include

This product is intended for indoor/outdoor applications. Ideal for high quality POS window decals, automotive window decals & temporary signage where easy removability is required. Excellent humidity & water resistance & good for most petroleum solvents and lower aliphatic alcohols.