



Wausau Coated Products, Inc.

Product Specification W011378

70# Dull Silver Foil Optimized For

HP Indigo Presses / PCT-524 / 40# SC

FACESTOCK DESCRIPTION: 70# Dull Silver Foil Optimized For HP Indigo Presses

Dull silver foil laminated to a paper base stock. Top coated and optimized for HP Indigo Presses. Can also be foil stamped and embossed. Typical end uses include high quality packaging such cosmetics, gourmet foods, wines, and gift items.

Basis Weight (25 x 38 / 500), lbs.	70.0
Caliper, mils	3.6
Tear, MD / CD, g	50 / 51
Tensile, MD / CD, lbs.	36 / 23

ADHESIVE DESCRIPTION: PCT-524

A very aggressive cold temperature permanent adhesive with great cold flow properties and an excellent choice for dairy label applications. PCT-524 will adhere to a frosted surface depending on the amount of frost and moisture present. Pretesting to determine end use applicability is recommended.

Type	Cold Temperature Permanent
Classification	Rubber Based
Minimum Application Temp., °F	+10
Service Temperature Range, °F	-40 to +150
Regulatory Compliances	California Proposition 65, CONEG, FDA 21 CFR 175.105, Natural Rubber Latex Free, REACH, RoHS

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	44.7
Caliper, mils	2.5
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	65
Tear, MD / CD, g	32 / 34
Tensile, MD / CD, lbs.	34 / 22
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, REACH, RoHS

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

