

Product: Rhino CA300 Aqueous Canvas Gloss



Category: Sign, Display & Digital - Aqueous

Country of Origin: Korea

Technical specifications:

Parameters	Unit	Range
Caliper	ums/mil	485 /19.4
Basis weight	g/m2	335
Base material	100% Bergin Cotton	
Surface	High Glossy	
Gloss	60° : 87.7 / 85° : 92.1 ASTM D2457	
Lab	90 / 0 / -1	ANSI T D50/2°/Abs/No

Guidelines

- Printing Tip** Dry time will vary depending on ink type. It is necessary to dry up and not to overlap the printed material.
- Lamination:** Lamination is optional. In order to protect the image from physical damage, overlaminates is recommended.
- Storage:** It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~30°C (50°~86°F), Humidity 35~65% RH
- Shelf Life:** One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

Conversion[†]

- | | |
|--|---|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminate |
| <input type="checkbox"/> Friction bed cutters | <input checked="" type="checkbox"/> Aqueous (dye & pigment) |
| <input type="checkbox"/> Die cutters | <input type="checkbox"/> Latex |
| <input type="checkbox"/> Thermal transfer screen | <input type="checkbox"/> Solvent |
| <input type="checkbox"/> Screen printing | <input type="checkbox"/> Eco Solvent |
| <input type="checkbox"/> Printing offset | <input checked="" type="checkbox"/> UV Ink jet |

[†]Always test with your combination of printer and inks prior to commercial use

Roll Sizes

914mm x 12m

139766

Common Applications

Photo & Portrait

Realistic prints and scrapbooks, albums and frames

Displays such as Posters, Billboards, Kiosks