Technical specification sheet

Ball & Doggett ballanddoggett.com.au

Product: Polycotton Canvas Premium Satin

Category: Display & Visual - Solvent, Eco Solvent, Latex and UV Ink jet

Country of Origin:

Technical specifications:

Paramaters	Range		
Yarn type	80% Polyester fabric & 20% Cotton fabric canvas		
Caliper	550um		
Weight	380gsm		
Coating Type	Knife-coated Solvent base Polymeric Resin (none heavy metal)		
Finish	Satin		
Whiteness	92 - 105		
Brightness	6+ / 2.0		
Opacity	94		
Shelf Time	2 years		
Application Temperture	≤ 100 °C		
Durability	≤ 12 months		

)						۰			
C	0	n	V	е	rs	П	0	n	т

☐ Flat bed cutters	Cold overlaminating
Friction bed cutters	□ Aqueous (dye & pigment)

☐ Friction bed cutters ☐ Aqueous (dy. ☐ Die cutters ☐ Latex

☐ Thermal transfer screen ☐ Solvent

□ Screen printing□ Printing offset□ UV Ink jet

Roll Sizes

1370mm x 30m 155322

Common	Applicat	ions

Fine art prints	Arts
Photographic imagery	Décor



⁺Always test with your combination of printer and inks prior to commerical use