

Product: SharkSkin Wet Strength Board

Category: Sign, Display & Digital - Rigid Media

Country of Origin: Australia

Technical specifications:

Specification

Weight	900gsm
Caliper	1500um
Smoothness (TAPPI 555)	1.0 +0.5 PPS (um)
Brightness (TAPPI 525/ ISO 2470)	84 ±2 Top (%)
Gloss 75° (TAPPI 480)	>40 Hunter 75° (%)
Cobb (1min) (TAPPI 441)	≥ 45 Top (g/m ²)
Cobb (2min) (TAPPI 441)	≥ 80 Back (g/m ²)
Moisture (TAPPI 442)	6.5 - 9.5 (%)
Wet Strength adhesive	Tubibond L 1593 Aqueous acrylic copolymer with specialty auxiliaries

Note:

1. Test Climate 23 ± 1°C and 50±2% RH (TAPPI 402)
2. Tolerances based upon 95% confidence limits (for pallets and reels)
3. All specifications mentioned above may be subjected to technical changes

Conversion⁺

- | | |
|---|---|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminating |
| <input type="checkbox"/> Friction fed cutters | <input type="checkbox"/> Aqueous |
| <input type="checkbox"/> Die cutting | <input type="checkbox"/> Latex inkjet |
| <input type="checkbox"/> Thermal transfer | <input type="checkbox"/> Eco Solvnt inkjet |
| <input type="checkbox"/> Screen printing | <input type="checkbox"/> Solvent inkjet |
| <input type="checkbox"/> Offset printing | <input checked="" type="checkbox"/> UV curable Inkjet |

*Always test with your combination of printer and inks prior to commercial use.

Sheet Size*

1220mm x 2440mm

* Made to order custom sizes

Common applications

POS Solutions

Posters

Promotional display re Fridgerated areas