Technical specification sheet

Product: Combo Plus - SP425 Category: Printing Blankets

Features

- Improved reboundability and striking absorption
- Increased flexibility, easy handling and machine set up
- Improvement of half tone reproduction and overall print quality
- Enhanced smash resistance
- Increased blanket lifetime

Application

Sheetded

Packaging

Technical Data

INK COMPATIBILITY	Hybrid
	Пурпа
PRINTING SURFACE COLOUR	Light Blue
THICKNESS (mm)	1.95
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	0,6
ELONGATION (%)	<0.9
TENSILE STRENGHTS (N/mm)	>60
WATER & SOLVENT PROTECTION	No
Ink Transfer	Suitable for printing using both UV and conventional inks

Cross Section

3 ply, 1,95mm thickness

Vulcan Combo Plus is available in 3 ply, 1,95 mm thickness.



The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Ball & Doggett, and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, Ball & Doggett makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms to its applicable current standard specifications. Standard specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS.

