

**Product: Printec Max 134 - SP429**

**Category: Printing Blankets**

## Features

- Precisely ground and buffed quick release surface
- Unique, thicker compressible layer
- Conventional and Hybrid ink compatible
- Reduced piling and linting
- Uniform gauge
- Compression construction
- Washes easily
- Defect-free surface

## Application

- Sheetfed
- Packaging

## Technical Data

<b>INK COMPATIBILITY</b>	Hybrid
<b>PRINTING SURFACE COLOUR</b>	Blue
<b>THICKNESS (mm)</b>	1,96
<b>AVERAGE LOAD VALUE N/cm<sup>2</sup> @ 0,23 mm Indentation</b>	240
<b>SURFACE ROUGHNESS (Ra micron)</b>	1.2
<b>WATER &amp; SOLVENT PROTECTION</b>	No
<b>Applications</b>	Improved ink release and cleaning

## Cross Section

3 ply, 1.96mm thickness

Printec 134 is available in 3 ply  
1,96 mm thickness



The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Ball & Doggett, and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, Ball & Doggett makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms to its applicable current standard specifications. Standard specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS.