

1.5 METRES DISTANCE

(makes the heart grow fonder)



DigiTuff EZ Floor

A textured, white, R10 slip resistant, Dry Toner print receptive, PET film with an optimised pressure sensitive adhesive for floor graphic applications.

- ✓ Unique sharkskin coating - toner bonding
- ✓ Scratch resistant durable surface, resists scuffing and stiletto heels
- ✓ No lamination required - PVC free
- ✓ Perfect for application to short-pile carpet tiles
- ✓ Easy to apply and easy to remove
- ✓ No distortion and no shrinkage even over time
- ✓ Available in 346gsm / 300ums
- ✓ Sheet size 320 x 450
- ✓ Plain, 2UP 205mm circle, 1UP 300mm circle

PROPERTY	TYPICAL VALUE	UNIT	TEST METHOD
Construction			
Total Thickness	300 +/- 6	μ	ISO 534
Total Weight	346 +/- 8	gsm	ISO 536
Face Material (without PSA)			
Thickness	153 +/- 4	μ	ISO 534
Weight	195 +/- 5	gsm	ISO 536
Adhesive			
Thickness	27 +/- 5	μ	ISO 534
180° Peel Adhesion (SS)	8.5 +/- 1.5	N/25mm	FINAT 1 (Modified) 25mm strip/ 30 min dwell
Adhesive Application Temperature	+5 to +50	°C	internal Method
Adhesive Service Temperature	-40 to +180	°C	internal Method
Liner			
Liner Thickness	120 +/- 3	μ	ISO 534
Liner Weight	130 +/- 3	gsm	ISO 536

RECOMMENDED CONDITIONS

Print Room	10°C - 30°C	30% - 65% RH
Usage	-40°C - 180°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

DIGITUFF EZ FLOOR

