Technical specficiation sheet Ball & Doggett

ballanddoggett.com.au

Product: Mastertac Dry Erase Lamination Film

 \bigvee aster \boxed{ac}


Category: Display & Visual

Technical specifications:

FEATURES AND ADVANTAGES:

- Clear high gloss PET film with adhesive back
- •Compatible to laminate on graphics, perfect for white board marker and dry-erased
- •Premium PET base, good weather resistance, excellent durable indoor use.


CONSTRUCTION DRAWING:



STANDARD SIZE:

1370mm x 50M 1520mm x 50M

PACKAGING:



REWRITABLE DATA:

- Re-writable length of time: minimum 20,000 times (tested with a whiteboard writing testing machine under ambient temperature and humidity)
- Erase Limitation: For normal whiteboard marker pen, marks can be dry erased off within one month. If the marker remains on the whiteboard beyond a month it can't be dry erased and will require additional cleaning solution; Whiteboard Cleaner or some alcoholic liquid.

ADHESION DATA:

GB/T 4852-2002– Test method for tack of pressure sensitive adhesive tapes by rolling ball 7#

PROCESS AND STORAGE:

- Working condition: temperature 15℃ to 30℃, and relative humidity 30% to 60%
- Storage condition: closed preserve avoiding sunlight, in temperature 10 $^{\circ}$ C to 35 $^{\circ}$ C, relative humidity 20% to 70%
- Shelf life: 12 months under storage condition. Unfinished material should be seal-packed.

PHYSICAL DATA:

Total thickness 140µm (±14)
Weight 140g/M2
Gloss 60° (±14) [95.
Water resistance 115] High
UV resistance Medium

Relative high temperature

Operating ranges:

Long term (days, weeks) 60°C Short term (minutes) 100°C

