

Product: Sumo SL-M02 PVC Free Unlined Mesh Banner 150gsm

Category: Signm, Display & Digital - Eco Solvent, Solvent, Latex & UV Inkjet

Technical specifications:

KEY FEATURES

// 1000Dx1000D 12x12/inch polyester mesh, 100% PVC free, environmentally friendly

// Max 197" width keeps it widely used in outdoor applications, eg. wall wrapping, building wrapping, fence, etc

// Please note this item is not able to be welded and liner option not available

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Average Weight	DIN EN ISO 2286-2, ASTM D751	150g/sq.m	/
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	1100x1100 dtex	1000x1000 denier
Number of Threads Per Unit	GB/T 4668	/	12x12/inch
Tensile Strength	DIN EN ISO 1421	1714x1533 N/5cm	196x175lbs/inch
Tear Strength	DIN 53363	683x721N	154x162lbs
Flame Resistance	DIN 4102-1-B1	Not available yet	
Available Width	DIN EN ISO 3759, ASTM D751-2006	Up to 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

Ink Printability⁺

- | | |
|---|--|
| <input type="checkbox"/> Flat bed cutters | <input checked="" type="checkbox"/> Dye Transfer |
| <input type="checkbox"/> Friction fed cutters | <input type="checkbox"/> Aqueous |
| <input type="checkbox"/> Die cutting | <input checked="" type="checkbox"/> Latex |
| <input type="checkbox"/> Offset printing | <input checked="" type="checkbox"/> Eco Solvnt |
| <input checked="" type="checkbox"/> Screen printing | <input checked="" type="checkbox"/> Solvent |
| <input checked="" type="checkbox"/> Dye direct | <input checked="" type="checkbox"/> UV Inkjet |

*Always test with your combination of printer and inks prior to commercial use.