

Technical Specification Sheet

Ball & Doggett

ballanddoggett.com.au

Product: Moroccan Backlit Fabric 120gsm

Category: Sign, Display & Digital - Latex, Dye Transfer & Dye Direct

FEATURES

- 100% polyester that has different coating on two sides, which allows you to print UV on one side and dye-sublimation on the other
- Super smooth surface, soft hand feel
- Better wrinkle resistance, good light transmission, makes your advertisement more attractive

PROPERTIES	TEST METHOD	DIN EN	METRIC	IMPERIAL
Total Weight	EN ISO 22886-2		120g/sq.m	3.5 oz/sq.yd
Base Fabric	DIN 60001		Polyester	Polyester
Weave Method	n.a.		Woven	
White Point CIE/D65	CIE 86/ASTM313-00(D65/10.SCI)		≥109	
Shrinkage	n.a.		≤3 % (190°C, 1min)	
Flame Resistance	/		DIN 4102-1-B1.NFPA 701	
Recommend Fixation	n.a.		190°C - 210°C - 1-2min	
Transfer Temp	n.a.		190°C - 210°C - 1-2min	
Yellowing Temp	SUPRKC REX C400		190°C	
Width	ASTM D751 2006		Max 320cm	126"
Standard Length	ASTM D751 2006		50m	55yd

PRINT TECHNOLOGY+

- | | | | |
|---|--|--|---|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Dry Toner | <input checked="" type="checkbox"/> Dye Transfer | <input type="checkbox"/> Eco Solvnt |
| <input type="checkbox"/> Friction fed cutters | <input type="checkbox"/> Aqueous | <input type="checkbox"/> Dye Direct | <input type="checkbox"/> Solvent |
| <input type="checkbox"/> Die cutting | <input type="checkbox"/> Screen printing | <input checked="" type="checkbox"/> Latex | <input checked="" type="checkbox"/> UV Inkjet |

*Always test with your combination of printer and inks prior to commercial use.

APPLICATIONS

/ Flag